



## HDU Valve against unintended car movement (UCM)

- Available for flow rate up to 600 l/min
- In according to EN 81.2 / 81.20-50
- Can also be installed on (stand-alone version) non OMARLIFT pump units
- Certified TÜV SÜD EN 81-2 81-20/50

<b>OMARLIFT</b> F.lli Kennedy, 22D - 24060 Bagnatica	
Tipo HDU / Type HDU HDU 600	
Materiale imp. / Job Nr.	<b>324634-02</b>
Data / Date	07-set-15
Portata / Flow range	600 l/min
Pressione stat. max. / Max.stat. press.	45 bar
LD 95/16/EC	LD 2014/03 EU
	0205
	EU-U-UCM 021



## Rupture valve

- Available for flow rate up to 600 l/min
- Available in different versions (3/4", 1" 1/4, 1" 1/2, 2")
- Certified by TÜV SÜD

<b>OMARLIFT</b> F.lli Kennedy, 22D - 24060 Bagnatica	
Tipo VP / Type VP VP 112-118	
Data / Date 07-set-15	
Materiale imp. / Job Nr.	<b>324634-02</b>
Flusso intervento / Tripping flow	599 l/min
Portata / Flow range	600-900 l/min
Pressione stat. max. / Max.stat. press.	80 bar
LD 95/16/EC	LD 2014/03 EU
0205	0036
ALBV 005	EU-RV 005